

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-9 (Canceled).

10. (Currently Amended) A microturbine engine comprising:  
a recuperator having a hot gas flow path and a cool gas flow path;  
a compressor providing a flow of compressed gas to the cool gas flow path of the recuperator, the compressed gas being heated within the recuperator;  
a source of fuel providing a flow of fuel;  
a combustor receiving the heated flow of compressed gas from the recuperator and the flow of fuel from the source of fuel, and combusting a mixture of compressed gas and fuel to produce a flow of hot gas;  
a radial flow turbine receiving the flow of hot gas from the combustor and discharging a flow of exhaust gas;  
a power transfer assembly including a turbine wheel constructed of a nickel alloy, a gear shaft constructed of a low-carbon carburized gear material and having a pinion gear integrally formed therein, and a transition portion between and welded to each of the turbine wheel and gear shaft, the turbine wheel being within the radial flow turbine and rotating in response to the flow of hot gas through the turbine;  
a bull gear in meshing engagement with the pinion gear and rotating in response to rotation of the pinion gear at a speed lower than the rotational speed of the power transfer assembly; and  
an electric generator and generating electricity in response to rotation of the bull gear.

11. (Original) The engine of claim 10, wherein the power turbine is constructed of AMS 5377 Inconel 713 LC; wherein the gear shaft is constructed of 9310 steel; and wherein the transition portion is constructed of 4140 steel.

12. (Currently Amended) The engine of claim 11, wherein the ~~gear shaft is carburized and includes an integral pinion gear that~~ meets the AGMA Q12 standard.

13. (Original) The engine of claim 10, wherein the transition portion is inertia welded to the power turbine and is electron beam welded to the gear shaft.

14. (Original) The engine of claim 13, wherein the inertia weld meets the MIL-STD-1252 standard and the electron beam weld meets the AMS 2681 standard.

15. (Original) The engine of claim 10, wherein the power turbine and gear shaft each have axes of symmetry that are collinear with each other, and wherein the power transfer assembly rotates about an axis of rotation that is substantially collinear with the axes of symmetry.

16. (Original) The engine of claim 10, wherein the gear shaft includes first and second bearing surfaces, the engine further comprising first and second bearings supporting the gear shaft at the first and second bearing surfaces for rotation at about 44,300 rpm.

17-23. (Canceled)